

Vydyne® 88X

polyamide 66/6 copolymer



Vydyne 88X is a medium-viscosity PA66/6 random copolymer used for extrusion-compounding. It provides benefits for compounds containing heat-sensitive additives and for end applications that require good surface finish. This copolymer is specifically designed to be used with FR packages and high mineral loadings. Vydyne 88X is the product of choice for low-yellowness-required applications.

Vydyne 88X maintains the chemical resistance typical of PA66/6 to many chemicals, machine and motor oils, solvents and gasoline.

Typical Applications/End Uses:
Compounding

General				
Material Status	• Commercial: Active			
Availability	• Asia Pacific	• Europe	• North America	
Features	• Abrasion Resistant • Chemical Resistant • Copolymer • Gasoline Resistant	• General Purpose • Good Toughness • High Rigidity • High Strength	• Oil Resistant • Solvent Resistant	
Uses	• Compounding • General Purpose			
Agency Ratings	• EC 1935/2004 • EU 10/2011	• EU 2023/2006 • FDA 21 CFR 177.1500		
Appearance	• Natural Color			
Forms	• Pellets			
Processing Method	• Compounding	• Compounding Extrusion		
Physical		Nominal Value	Unit	Test Method
Density		1.14	g/cm ³	ISO 1183
Viscosity Number (H ₂ SO ₄ (Sulphuric Acid))		137 to 148	cm ³ /g	ISO 307
Bulk Density		674	g/l	ASTM D1895
Moisture Content		0.50	%	ASTM D6869
Relative Viscosity ²		45.0 to 51.0		ASTM D789
Thermal		Nominal Value	Unit	Test Method
Melting Temperature		255	°C	ISO 11357-3
Optical		Nominal Value	Unit	Test Method
Yellowness Index		-4.0	YI	ASTM D1925

Notes

Typical properties: these are not to be construed as specifications.

¹ Typical properties: these are not to be construed as specifications.

² Formic acid



North America

+1 888 927 2363

Europe

+32 10 608 600

Asia

+86 21 6340 3300

Disclaimer of Warranty and Liability

NOTICE: Although the information and recommendations set forth herein (hereinafter "information") are presented in good faith and believed to be correct as of the date hereof, Ascend Performance Materials Operations LLC makes no representations or warranties as to the completeness or accuracy thereof.

Information is supplied upon the condition that the persons receiving same will make their own determination as to its suitability for their purposes prior to use. In no event will Ascend Performance Materials Operations LLC be responsible for damages of any nature whatsoever resulting from the use of or reliance upon information or the products to which information refers. Nothing contained herein is to be construed as a recommendation to use any product, equipment or formulation in conflict with any patent, and Ascend Performance Materials Operations LLC makes no representation or warranty, express or implied, that use thereof will not infringe any patent. No representations or warranties, either express or implied, of merchantability, fitness for a particular purpose or of any other nature are made hereunder with respect to information or the product to which information refers.